



Just Listen.

Phone: 866-787-7881

Fax: 815-364-0242

atsinfo@atsacoustics.com

www.atsacoustics.com

ATS Acoustic Panels



Solve your acoustical and aesthetic needs with ATS Acoustic Panels. Featuring superior sound control performance and endless customization options, our standard panels offer effective sound absorption specifically designed for your environment.

Ideal for schools, conference rooms, restaurants, churches, or anywhere a high-quality, affordable sound control is needed.

Available dimensions: 24"x24", 24"x36", 24"x48", 48"x96", and Custom-Specified Sizes.

Available in 1", 2", and 4" thicknesses.

Key Features

- NRC (Noise Reduction Coefficient) ratings of 1.00 to 1.15 for superior sound absorption.
- Core Material: Roxul Acoustical Fire Batt – Mineral Wool.
- Durable beveled or squared edges provide clean, attractive lines that resist wear and tear better than chemically hardened fiberglass panels.



Village Tavern, MA

Easy-to-Install, Durable Design

- Solid internal-edge frame features impact-resistant construction.
- Flush-mount hardware installs securely and neatly.

Available Customizations

- Custom shapes and custom sizes built to your specifications.
- ATSM E84 Class A fire rating option available.
- Available in a range of colors or custom-specified fabrics.



Frisco Bible Church, TX

1/3 Octave Band Center Frequencies, HZ

Panel Thickness	125	250	500	1000	2000	4000	NRC
2"	0.12	0.67	1.17	1.12	1.08	1.08	1.00

Data from independent testing of this item by RAL, a leading acoustical laboratory